


NEW YORK • LONDON

475 Barell Ave., Carlstadt, NJ 07072 Voice: 800-230-9497, 201-549-1160

Fax: 201-549-1161

QolorFLEX 5050-12-RGBI-60-5-20-1 is an interior grade hybrid LED Tape with a high output brightness and the ability to create a full spectrum of colors when used with a DMX control system. It is available in full 5 meter spools, sample strips and is included in our QolorFLEX Demo Kit.





QolorFLEX LED Tape P/N 5050-12-RGBI-60-5-20-1

SPECIFICATIONS

or EditioAttono	
Color(s)	RGB+Indigo
Color Temp	N/A
	622/518/468/450
Beam Angle	120°
Brightness (lumens/m)	400
Power Consumption (watts/5m)	50.4
Power Consumption (watts/ft)	3.07
Operating Voltage	12VDC
Current (mA/5m)	4200
Quantity of LEDs Per 5m (16.4 ft)	300
CRI	N/A
LED Spacing	16.7
Cutting Increment	100.0mm
Length	5m (16.4 ft)
Width	12mm
Average Life	25,000 hrs
Compliance	ETL
Warranty	Two Years
IP Rating	IP20
LED Chip Size	5050
Backing Color	White
Use Environment	Indoor